

NOTES:

- 10 TO BE USED WITH MINERAL BASE HYDRAULIC OIL ONLY.
 2) DIMENSIONS MAY VARY BETWEEN UNITS AND ARE TO BE USED FOR REFERENCE PURPOSES ONLY. MILLIMETER VALUES MAY NOT BE AN EXACT CONVERSION OF INCH VALUES.
 3) APPLY A MOLY BASE GREASE THRU ZERK FITTING AFTER ASSEMBLY UNTIL GREASE IS OBSERVED EXITING SEALS.
 4) BRAKE SHOWN IN THE HYDRAULICALLY APPLIED POSITION.
 5) BRAKE SURFACE FINISH: ZINC CHROMATE YELLOW PER ASTM B633, TYPE II, SC2 6) LINING MATERIAL: NON-ASBESTOS, LEAD FREE
 7) SEAL KIT P/N 02-500-058.
 8) REPAIR KIT P/N 02-500-224.
 9) LINING KIT P/N 20-060-113.

- 9) LINING KIT P/N 20-060-113. 10) UNIT COMES WITH SAE 37° (JIC) #4 STRAIGHT O-RING ADAPTOR.

PERFORMANCE CHARACTERISTICS: 1) BRAKE TORQUE: Bt (LBIN) = 3840 X (DISC RADIUS - 1.18) 2) MAXIMUM TORQUE ACHIEVED ONLY AFTER BRAKE HAS BEEN PROPERLY ADJUSTED AND BURNISHED. 3) COMPLETE RETRACTION PESSURE: 1,500 PSI. 4) MAXIMUM CONTINUOUS DUTY PRESSURE IS 2000 PSI. 5) MAXIMUM INTERMITTENT DUTY PRESSURE IS 2500 PSI. 6) VOLUME REQUIRED FOR COMPLETE RETRACTION: .80 CU IN. MAXIMUM. 7) CAUTION: DISC RUBBING SPEED SHOULD NOT EXCEED 5,000 FT./MIN. 8) "A" DIMENSION = DISC RADIUS + 2.38 INCHES (DISC DIA. FROM 9 TO 15 INCHES). "A" DIMENSION = DISC RADIUS + 2.50 INCHES (DISC DIA. GREATER THAN 15 INCHES).

- - INC ARE BASED ON INFORMATION SUPPLIED BY POTENTIAL THE MATERIAL DISCLOSED IN THIS DOCUMENT. USER AND/OR SYSTEM DESIGNER. THE POTENTIAL USER AND/OR DESIGNER MUST MAKE FINAL ACCEPTANCE AND APPROVAL OF AND MAY NOT BE REPRODUCED OR DISCLOSED

COMPONENT AND SYSTEM RECOMMENDATIONS MADE BY MICO, MICO, INC CLAIMS PROPRIETARY RIGHTS TO THIS DOCUMENT IS PROVIDED IN CONFIDENCE COMPONENTS AND SYSTEM AFTER TESTING PERFORMANCE ON | WITHOUT WRITTEN PERMISSION FROM MICO, INC. AN ACTUAL APPLICATION FOR WHICH SYSTEM WAS DESIGNED. | COPYRIGHT MICO, INC. ALL RIGHTS RESERVED.



0	SCALE 0.750	TITLE SPRING BRAKE				
E D	DWN JJC 2015-07-08	APVD PROD ENGRG	SIZE	DRAWING		RE۱
	X NO	APVD ENGRG BSW 2015-07-10	В	01-530-628 CUSTOMER COPY		G ¹³