



NOTES:

1. USE MINERAL BASE HYDRAULIC OIL ONLY FOR BRAKE RELEASE
2. DIMENSIONS MAY VARY BETWEEN UNITS AND ARE FOR REFERENCE PURPOSES ONLY
MILLIMETER VALUES MAY NOT BE AN EXACT CONVERSION OF INCH VALUES
3. LINING REPAIR KIT P/N 02-500-083
4. O-RING REPAIR KIT P/N 02-500-153
5. SPRING REPAIR KIT P/N 02-500-154

SPECIFICATIONS:

DRY MULTIPLE DISC BRAKE, SPRING APPLY, HYDRAULIC RELEASE

TORQUE RATING: 4.200 LBIN STATIC (BREAKAWAY) AT O PSI BACK PRESSURE

RELEASE PRESSURE: 230 PSI INITIAL. 300 PSI FULL

MAXIMUM OPERATING PRESSURE: 3.000 PSI MAXIMUM SPEED: 1.000 RPM LINING MATERIAL: SINTERED BRONZE

APPROXIMATE WEIGHT:

INCH [MILLIMETER]



THIS DOCUMENT IS PROVIDED IN CONFIDENCE COMPONENTS AND SYSTEM AFTER TESTING PERFORMANCE ON | WITHOUT WRITTEN PERMISSION FROM MICO, INC. AN ACTUAL APPLICATION FOR WHICH SYSTEM WAS DESIGNED. | COPYRIGHT MICO, INC. ALL RIGHTS RESERVED.



SCALE 0.500	TITLE MN-1342 CLOSED OUTPUT MOTOR BRAKE			
DWN RGBS1	APVD PROD ENGRG		DRAWING NUMBER	REV
2010-03-02 X NO	APVD ENGRG	В	02-550-114	М
	RV 2010-03-02		CUSTOMER COPY	1 H