

NOTES:

1. USE MINERAL BASE HYDRAULIC OIL ONLY FOR BRAKE RELEASE
2. DIMENSIONS MAY VARY BETWEEN UNITS AND ARE FOR REFERENCE PURPOSES ONLY
MILLIMETER VALUES MAY NOT BE AN EXACT CONVERSION OF INCH VALUES
3. LINING REPAIR KIT P/N 02-500-083
4. O-RING REPAIR KIT P/N 02-500-153
5. SPRING REPAIR KIT P/N 02-500-154

SPECIFICATIONS:

DRY MULTIPLE DISC BRAKE. SPRING APPLY. HYDRAULIC RELEASE


TORQUE RATING: 2.500 LBIN STATIC (BREAKAWAY) AT 0 PSI BACK PRESSURE

RELEASE PRESSURE: 120 PSI INITIAL, 150 PSI FULL

MAXIMUM OPERATING PRESSURE: 3.000 PSI MAXIMUM SPEED: 1.000 RPM LINING MATERIAL: SINTERED BRONZE

APPROXIMATE WEIGHT:

INCH [MILLIMETER]



THIS DOCUMENT IS PROVIDED IN CONFIDENCE AN ACTUAL APPLICATION FOR WHICH SYSTEM WAS DESIGNED. | COPYRIGHT MICO, INC. ALL RIGHTS RESERVED.

			,
North	Mankato,	Minnesota	US
		MM 430E	

SCALE 0.500	CLOSED OUTPUT MOTOR BRAKI					
DWN RGBS1 2010-03-02	APVD PROD ENGRG PJS 2010-04-05	SIZE	DRAWING NUMBER	REV		
X NO	APVD ENGRG	В	02-550-120	Н		
	RV 2010-03-02		CUSTOMER COPY	0 н		