


**NOTES:**

- FOR USE WITH MINERAL BASE HYDRAULIC OIL ONLY
- DIMENSIONS WITHOUT TOLERANCE MAY VARY BETWEEN UNITS AND ARE FOR REFERENCE PURPOSES ONLY  
MILLIMETER VALUES MAY NOT BE AN EXACT CONVERSION OF INCH VALUES
- REPAIR KIT P/N 12-501-399

**SPECIFICATIONS:**

TYPE:	MULTIPLE DISC BRAKE, SPRING APPLY, HYDRAULIC RELEASE (WITH PRESSURE OVERRIDE)
FAILSAFE SECTION: TORQUE RATING:	1,500 LBIN STATIC (BREAKAWAY) AT 0 PSI BACK PRESSURE ACTUAL TORQUE MAY VARY BY UP TO 10% DUE TO MANUFACTURING TOLERANCES.
RELEASE PRESSURE:	85 PSI INITIAL, 110 PSI FULL 3,000 PSI MAX. (CONTINUOUS)
SERVICE OVERRIDE SECTION: TORQUE RATING:	1,600 LBIN @ 600 PSI ACTUAL TORQUE MAY VARY BY UP TO 10% DUE TO MANUFACTURING TOLERANCES.
MAXIMUM INPUT PRESSURE:	1,000 PSI
MAXIMUM SPEED:	3,000 RPM, HOWEVER, MAXIMUM SPEED AT TIME OF SERVICE APPLY IS DEPENDENT ON PRODUCT APPLICATION.
LINING MATERIAL:	AUTOMOTIVE TYPE, INTEGRALLY MOLDED
VOLUME OF OIL REQUIRED: TO RELEASE BRAKE	0.75 IN <sup>3</sup> MIN., 0.95 IN <sup>3</sup> MAX.
APPROXIMATE WEIGHT:	26 LB



VIEW A-A

INCH  
[MILLIMETER]

<b>MICO</b> a WABCO company				
SCALE 0.500	TITLE LMB-131315-BP MULTIPLE DISC BRAKE WITH PRESSURE OVERRIDE	SIZE B	DRAWING NUMBER 02-556-398	REV N
DWNSHYPO 2016-08-25	APVD PROD ENGRG MG 2017-01-03			
X NO X6678	APVD ENGRG RV 2016-09-12		CUSTOMER COPY	1

COMPONENT AND SYSTEM RECOMMENDATIONS MADE BY MICO, INC ARE BASED ON INFORMATION SUPPLIED BY POTENTIAL USER AND/OR SYSTEM DESIGNER. THE POTENTIAL USER AND/OR DESIGNER MUST MAKE FINAL ACCEPTANCE AND APPROVAL OF COMPONENTS AND SYSTEM AFTER TESTING PERFORMANCE ON AN ACTUAL APPLICATION FOR WHICH SYSTEM WAS DESIGNED.

MICO, INC CLAIMS PROPRIETARY RIGHTS TO THE MATERIAL DISCLOSED IN THIS DOCUMENT. THIS DOCUMENT IS PROVIDED IN CONFIDENCE AND MAY NOT BE REPRODUCED OR DISCLOSED WITHOUT WRITTEN PERMISSION FROM MICO, INC. COPYRIGHT MICO, INC. ALL RIGHTS RESERVED.