

6. SPRING REPAIR KIT P/N 12-501-518
7. STACK ARRANGEMENT: ROTOR/STATOR/ROTOR/STATOR
8. BRAKE SURFACE COATING: GREY GLOSSY POLYURETHANE PAINT.
9. SPRING COMBINATION: 10 RED SPRINGS
10. RECOMMENDED CASE OIL: CHEVRON DELO GEAR LUBRICANT ESI SAE 80W-90.
GEAR LUBRICANTS CONTAINING SULFUR-PHOSPHORUS BASED EP ADDITIVES
SHOULD BE AVOIDED DUE TO LONG TERM EFFECTS ON FRICTION MATERIAL.
11. GENIE INDUSTRIES P/N 119558

## SPECIFICATIONS: TYPE: WE

WET MULTIPLE DISC BRAKE. SPRING APPLY. HYDRAULIC RELEASE.

MAXIMUM SPEED:

4.000 RPM SHAFT SPEED CAPABILITY SPECIFIED IS FOR BRAKE IN RELEASED CONDITION. ENERGY ABSORPTION DURING APPLY CYCLE MUST BE CAREFULLY EXAMINED FOR EACH APPLICATION.

RELEASE PRESSURE: 240 PSI INITIAL. 290 PSI FULL. 3.000 PSI MAX.

LINING MATERIAL: SINTERED BRONZE

TORQUE RATING:

2.000 LBIN STATIC (BREAKAWAY) AT 0 PSI BACK PRESSURE ACTUAL TORQUE MAY VARY BY UP TO 10% DUE TO MANUFACTURING TOLERANCES.

VOLUME OF OIL REQUIRED: TO RELEASE BRAKE

0.5 IN.<sup>3</sup> MIN., 0.9 IN.<sup>3</sup> MAX.

APPROXIMATE WEIGHT: 24.5 LB

**INCH** [MILLIMETER]



COMPONENT AND SYSTEM RECOMMENDATIONS MADE BY MICO, MICO, INC CLAIMS PROPRIETARY RIGHTS TO INC ARE BASED ON INFORMATION SUPPLIED BY POTENTIAL | THE MATERIAL DISCLOSED IN THIS DOCUMENT. USER AND/OR SYSTEM DESIGNER. THE POTENTIAL USER AND/OR THIS DOCUMENT IS PROVIDED IN CONFIDENCE DESIGNER MUST MAKE FINAL ACCEPTANCE AND APPROVAL OF AND MAY NOT BE REPRODUCED OR DISCLOSED COMPONENTS AND SYSTEM AFTER TESTING PERFORMANCE ON WITHOUT WRITTEN PERMISSION FROM MICO, INC. AN ACTUAL APPLICATION FOR WHICH SYSTEM WAS DESIGNED. COPYRIGHT MICO, INC. ALL RIGHTS RESERVED.

	SCALE 0.500	TITLE MI		3-131330-NZ E DISC BRAKE	
ı	DWN RGBS1 2012-02-08	APVD PROD ENGRG PJS 2013-03-27	SIZE	DRAWING NUMBER	REV
	X NO	APVD ENGRG	В	02-556-448	C
		RV 12/09/12		CUSTOMER COPY	0