



**NOTES:**  
 1) FOR USE WITH MINERAL BASE HYDRAULIC OIL ONLY.  
 2) DIMENSIONS MAY VARY BETWEEN UNITS AND ARE FOR REFERENCE PURPOSES ONLY. MILLIMETER VALUES MAY NOT BE AN EXACT CONVERSION OF INCH VALUES.  
 3) VALVE SURFACE COATING: SEMI-GLOSS BLACK POLYURETHANE ENAMEL PAINT.

**PERFORMANCE CHARACTERISTICS:**  
 1) VALVE PRESSURE SETTING IS 1500 ±50 PSI [103 ±3 bar] WITH 2000 PSI [138 bar] INLET PRESSURE AND 15 cSt OIL.  
 2) MAXIMUM INLET PRESSURE IS 3000 PSI [207 bar].  
 3) OPERATING TEMPERATURE RANGE: -40 °F TO 225 °F.

**SERVICE PARTS:**  
 1) VALVE ASSEMBLY P/N 20-100-907.  
 2) REPAIR KIT P/N 06-400-150.

COMPONENT AND SYSTEM RECOMMENDATIONS MADE BY MICO, INC ARE BASED ON INFORMATION SUPPLIED BY POTENTIAL USER AND/OR SYSTEM DESIGNER. THE POTENTIAL USER AND/OR DESIGNER MUST MAKE FINAL ACCEPTANCE AND APPROVAL OF COMPONENTS AND SYSTEM AFTER TESTING PERFORMANCE ON AN ACTUAL APPLICATION FOR WHICH SYSTEM WAS DESIGNED.		MICO, INC CLAIMS PROPRIETARY RIGHTS TO THE MATERIAL DISCLOSED IN THIS DOCUMENT. THIS DOCUMENT IS PROVIDED IN CONFIDENCE AND MAY NOT BE REPRODUCED OR DISCLOSED WITHOUT WRITTEN PERMISSION FROM MICO, INC. COPYRIGHT MICO, INC. ALL RIGHTS RESERVED.	
SCALE 0.500	TITLE REVERSE MODULATING VALVE	SIZE C	DRAWING NUMBER 03-460-445
DWN ETM 2013-04-29	APVD PROD ENGRG JC 2013-07-18	REV C	CUSTOMER COPY
X NO X09-3038-000	APVD ENGRG JC 2013-07-18		

