



NOTES:

- 1) TO BE USED WITH MINERAL BASE HYDRAULIC OIL ONLY.
- 2) MILLIMETER VALUES MAY NOT BE AN EXACT CONVERSION OF INCH VALUES.
- 3) MOUNT WITH AIR EXHAUST DOWN
- 4) VALVE FINISH: ANODIZED ALUMINUM

PERFORMANCE CHARACTERISTICS:

- 1) APPROXIMATELY 100 PSI HYDRAULIC PILOT INPUT PRESSURE TO START AIR OUTPUT.
- 2) APPROXIMATELY 100 PSI AIR OUTPUT WITH 875 PSI HYDRAULIC INPUT.
- 3) PILOT VOLUME (P) IS .04 CUIN MAX.

INCH
[MILLIMETER]

		SCALE		
		0.875		
TITLE		SIZE	DRAWING NUMBER	REV
HYDRAULIC/AIR RELAY VALVE		B	03-469-002	D
DWN JJH 2017-07-12	APVD PROD ENGRG	B	03-469-002	D
X NO X08-2145-000	APVD ENGRG BSW 2017-10-30			
CUSTOMER COPY				

COMPONENT AND SYSTEM RECOMMENDATIONS MADE BY MICO, INC. ARE BASED ON INFORMATION SUPPLIED BY POTENTIAL USER AND/OR SYSTEM DESIGNER. THE POTENTIAL USER AND/OR DESIGNER MUST MAKE FINAL ACCEPTANCE AND APPROVAL OF COMPONENTS AND SYSTEM AFTER TESTING PERFORMANCE ON AN ACTUAL APPLICATION FOR WHICH SYSTEM WAS DESIGNED.

MICO, INC. CLAIMS PROPRIETARY RIGHTS TO THE MATERIAL DISCLOSED IN THIS DOCUMENT. THIS DOCUMENT IS PROVIDED IN CONFIDENCE AND MAY NOT BE REPRODUCED OR DISCLOSED WITHOUT WRITTEN PERMISSION FROM MICO, INC. COPYRIGHT MICO, INC. ALL RIGHTS RESERVED.