

NOTES:

- 1. FOR USE WITH MINERAL BASE HYDRAULIC OIL ONLY.
 2. DIMENSIONS MAY VARY BETWEEN UNITS AND ARE FOR REFERENCE PURPOSES ONLY.
 MILLIMETER VALUES MAY NOT BE AN EXACT CONVERSION OF INCH VALUES.
 3. REPAIR KIT P/M: 06-400-084
 4. SURFACE COATING: OLIVE DRAB PRIMER PER DOD-P-15328 SPECIFICATION.

PERFORMANCE CHARACTERISTICS:

- 1. RECOMMENDED SYSTEM FLOW IS 2 TO 35 GPM [8 TO 132 LPM].
 2. FLOW THRU PRESSURE DROP IS APPROXIMATELY 20 PSI [1 BAR] AT 35 GPM [132 LPM] WITH 14 CENTISTOKE OIL.
 3. INTERNAL FILTRATION IS 54 MICRON OR BETTER.
 4. EXTERNAL FILTRATION OF 10 MICRON OR BETTER IS RECOMMENDED.



INC ARE BASED ON INFORMATION SUPPLIED BY POTENTIAL THE MATERIAL DISCLOSED IN THIS DOCUMENT. USER AND/OR SYSTEM DESIGNER. THE POTENTIAL USER AND/OR DESIGNER MUST MAKE FINAL ACCEPTANCE AND APPROVAL OF AND MAY NOT BE REPRODUCED OR DISCLOSED COMPONENTS AND SYSTEM AFTER TESTING PERFORMANCE ON | WITHOUT WRITTEN PERMISSION FROM MICO, INC. AN ACTUAL APPLICATION FOR WHICH SYSTEM WAS DESIGNED. COPYRIGHT MICO, INC. ALL RIGHTS RESERVED.

COMPONENT AND SYSTEM RECOMMENDATIONS MADE BY MICO, MICO, INC CLAIMS PROPRIETARY RIGHTS TO THIS DOCUMENT IS PROVIDED IN CONFIDENCE

,	SCALE TITLE ACV-SM013					
	DWN JJH 2010-11-02	APVD PROD ENGRG DPD 2010-11-03		DRAWING		REV
	X NO SEE CHART	APVD ENGRG PWB 2010-11-02	В	89-460-005 CUSTOMER COPY		۰A