

NOTES:

1. LINING REPAIR KIT P/N 12-501-245
2. BEARING REPAIR KIT P/N 12-501-241
3. O-RING REPAIR KIT P/N 12-501-248
4. SPRING REPAIR KIT P/N 12-501-248
5. REFER TO INSTALLATION SHEET P/N 81-538-002 (SUPPLIED WITH BRAKE)
FOR FURTHER MOUNTING INSTRUCTIONS.
6. DIMENSIONS MAY VARY BETWEEN UNITS AND ARE TO BE USED FOR
REFERENCE PURPOSES ONLY. MILLIMETER VALUES MAY NOT BE AN
EXACT CONVERSION OF INCH VALUES.

SPECIFICATIONS:

RELEASE PRESSURE:


TYPE: DRY MULTIPLE DISC BRAKE, SPRING APPLY, HYDRAULIC RELEASE

150 PSI INITIAL. 180 PSI FULL

TORQUE RATING: 3.500 LBIN STATIC (BREAKAWAY) AT O PSI BACK PRESSURE

MAXIMUM OPERATING PRESSURE: 3.000 PSI MAXIMUM SPEED: 3.900 RPM APPROXIMATE WEIGHT: 27 LB

TO BE USED WITH MINERAL BASE HYDRAULIC OIL ONLY.



SECTION A-A



COMPONENT AND SYSTEM RECOMMENDATIONS MADE BY MICO, MICO, INC CLAIMS PROPRIETARY RIGHTS TO INC ARE BASED ON INFORMATION SUPPLIED BY POTENTIAL THE MATERIAL DISCLOSED IN THIS DOCUMENT. USER AND/OR SYSTEM DESIGNER. THE POTENTIAL USER AND/OR DESIGNER MUST MAKE FINAL ACCEPTANCE AND APPROVAL OF AND MAY NOT BE REPRODUCED OR DISCLOSED COMPONENTS AND SYSTEM AFTER TESTING PERFORMANCE ON | WITHOUT WRITTEN PERMISSION FROM MICO, INC. AN ACTUAL APPLICATION FOR WHICH SYSTEM WAS DESIGNED. COPYRIGHT MICO, INC. ALL RIGHTS RESERVED.

THIS DOCUMENT IS PROVIDED IN CONFIDENCE

+	SCALE TITLE MULTIPLE DISC BRAKE 0.500 3A-060635-MV				
1					
	DWN MAP	APVD PROD ENGRG	SIZE	DRAWING NUMBER	REV
, [2009-09-15	PJS 2009-11-02	_	12 520 200	
	X NO	APVD ENGRG	B	13-538-298	В
	•	BLF 2009-09-15		CUSTOMER COPY	1 2