



**NOTES:**

- 1) LINING REPAIR KIT P/N 12-501-245
- 2) BEARING REPAIR KIT P/N 12-501-241
- 3) O-RING REPAIR KIT P/N 12-501-246
- 4) SPRING REPAIR KIT P/N 12-501-244
- 5) REFER TO INSTALLATION SHEET #81-538-002 (SUPPLIED WITH BRAKE) FOR FURTHER MOUNTING INSTRUCTIONS.

**SPECIFICATIONS:**

<b>TYPE:</b>	DRY MULTIPLE DISC BRAKE, SPRING APPLY, HYDRAULIC RELEASE
<b>TORQUE RATING:</b>	3,500 IN. LBS. STATIC (BREAKAWAY) AT 0 PSI BACK PRESSURE
<b>RELEASE PRESSURE:</b>	170 PSI INITIAL, 200 PSI FULL
<b>MAXIMUM OPERATING PRESSURE:</b>	3,000 PSI
<b>MAXIMUM SPEED:</b>	3,900 R. P. M.
<b>APPROXIMATE WEIGHT:</b>	27 LBS.
FOR USE WITH MINERAL BASE HYDRAULIC OIL ONLY	

<b>MICO</b> North Mankato, Minnesota U.S.A.		
SCALE 1:2	PART NUMBER 13-538-372	REV. C
X NO. x6273	CUSTOMER COPY	
DRAWN G. J.		
REVISED LH		
DATE 8/6/98	CHECKED	APPROVED ENG.

MICO, INC. CLAIMS PROPRIETARY RIGHTS TO THE MATERIAL DISCLOSED IN THIS DOCUMENT. THIS DOCUMENT IS PROVIDED IN CONFIDENCE AND MAY NOT BE REPRODUCED OR DISCLOSED WITHOUT WRITTEN PERMISSION FROM MICO, INC. COPYRIGHT MICO, INC. ALL RIGHTS RESERVED.