



- NOTES:**
1. FOR USE WITH MINERAL BASE HYDRAULIC OIL ONLY
  2. DIMENSIONS MAY VARY BETWEEN UNITS AND ARE FOR REFERENCE PURPOSES ONLY. MILLIMETER VALUES MAY NOT BE AN EXACT CONVERSION OF INCH VALUES.
  3. BEARING REPAIR KIT P/N 12-501-104
  4. LINING REPAIR KIT P/N 12-501-100
  5. SPRING REPAIR KIT P/N 12-501-102
  6. O-RING REPAIR KIT P/N 12-501-098
  7. PISTON REPAIR KIT P/N 12-501-240
  8. REPAIR KIT P/N 12-501-287
  9. FOR USE WITH A DANA SPICER MODEL 70 AXLE
  10. TORQUE ALL 4 BOLTS TO 80-90 LBFT AFTER ASSEMBLY OF BRAKE ON VEHICLE.

**SPECIFICATIONS:**

TYPE: DRY MULTIPLE DISC BRAKE, SPRING APPLY, HYDRAULIC RELEASE

RELEASE PRESSURE: 280 PSI INITIAL, 360 PSI FULL  
ACTUAL TORQUE MAY VARY BY UP TO 10% DUE TO MANUFACTURING TOLERANCES.

TORQUE RATING : 17,000 LBIN STATIC (BREAKAWAY)

VOLUME DISPLACEMENT TO RELEASE BRAKE: 1.2 CU. IN

APPROXIMATE WEIGHT : 44 LBS

<b>MICO</b> <sup>®</sup>			
North Mankato, Minnesota USA			
SCALE 1.000	TITLE S-004517-S MULTIPLE DISC BRAKE		REV J
DWNSHYPO 2016-04-18	APVD PROD ENGRG PJS 2016-04-26	SIZE B	DRAWING NUMBER 13-545-234
X NO	APVD ENGRG RV 2016-04-20	CUSTOMER COPY	

COMPONENT AND SYSTEM RECOMMENDATIONS MADE BY MICO, INC ARE BASED ON INFORMATION SUPPLIED BY POTENTIAL USER AND/OR SYSTEM DESIGNER. THE POTENTIAL USER AND/OR DESIGNER MUST MAKE FINAL ACCEPTANCE AND APPROVAL OF COMPONENTS AND SYSTEM AFTER TESTING PERFORMANCE ON AN ACTUAL APPLICATION FOR WHICH SYSTEM WAS DESIGNED.

MICO, INC CLAIMS PROPRIETARY RIGHTS TO THE MATERIAL DISCLOSED IN THIS DOCUMENT. THIS DOCUMENT IS PROVIDED IN CONFIDENCE AND MAY NOT BE REPRODUCED OR DISCLOSED WITHOUT WRITTEN PERMISSION FROM MICO, INC. COPYRIGHT MICO, INC. ALL RIGHTS RESERVED.