

NOTES:

1. FOR USE WITH MINERAL BASE HYDRAULIC DIL ONLY
2. LINING REPAIR KIT P/N 12-501-004
3. BEARING REPAIR KIT P/N 12-501-006
4. O-RING REPAIR KIT P/N 12-501-002
5. SPRING REPAIR KIT P/N 12-501-008

## **SPECIFICATIONS**:

DRY MULTIPLE DISC BRAKE, SPRING APPLY, HYDRAULIC RELEASE 9800 LBIN STATIC (BREAKAWAY) AT 0 PSI BACK PRESSURE 210 PSI INITIAL, 290 PSI FULL TYPE: TORQUE RATING: RELEASE PRESSURE: MAXIMUM OPERATING PRESSURE:

PRESSURE: 3000 PSI
MAXIMUM SPEED: 3900 RPM
LINING MATERIAL: SINTERED BRONZE
APPROXIMATE WEIGHT: 40 LB

## INCH [MILLIMETER]



COMPONENT AND SYSTEM RECOMMENDATIONS MADE BY MICO, MICO, INC CLAIMS PROPRIETARY RIGHTS TO INC ARE BASED ON INFORMATION SUPPLIED BY POTENTIAL THE MATERIAL DISCLOSED IN THIS DOCUMENT. USER AND/OR SYSTEM DESIGNER. THE POTENTIAL USER AND/OR DESIGNER MUST MAKE FINAL ACCEPTANCE AND APPROVAL OF AND MAY NOT BE REPRODUCED OR DISCLOSED COMPONENTS AND SYSTEM AFTER TESTING PERFORMANCE ON | WITHOUT WRITTEN PERMISSION FROM MICO, INC. AN ACTUAL APPLICATION FOR WHICH SYSTEM WAS DESIGNED. | COPYRIGHT MICO, INC. ALL RIGHTS RESERVED.

THIS DOCUMENT IS PROVIDED IN CONFIDENCE

1					
	SCALE 0.500	MULTIPLE DISC BRAKE			
	DWN MAP 2008-12-10	APVD PROD ENGRG PJS 2009-07-06	SIZE	DRAWING NUMBER	REV
	X NO	APVD ENGRG	_	13-547-324	E,
	•	RV 2009-02-09		CUSTOMER COPY	<u> </u>