

## **NOTES:**

1.) LINING REPAIR KIT P/N 12-501-014

2.) BEARING REPAIR KIT P/N 12-501-006

3.) O-RING REPAIR KIT P/N 12-501-002

4.) 30RING REPAIR KIT P/N 12-501-008

## **SPECIFICATIONS:**

TYPE: DRY MULTIPLE DISC BRAKE, SPRING APPLY, HYDRAULIC RELEASE

TORQUE RATING: 6,600 LB-IN STATIC (BREAKAWAY) AT 0 PSI BACK PRESSURE


RELEASE PRESSURE: 130 PSI INITIAL, 180 PSI FULL

MAXIMUM OPERATING

PRESSURE: 3,000 PSI MAXIMUM SPEED: 3,900 RPM

APPROXIMATE WEIGHT: 40 LBS.

FOR USE WITH MINERAL BASE HYDRAULIC OIL ONLY.



COMPONENT AND SYSTEM RECOMMENDATIONS MADE BY MICO, MICO, INC. CLAIMS PROPRIETARY RIGHTS TO INC. ARE BASED ON INFORMATION SUPPLIED BY POTENTIAL USER AND/OR SYSTEM DESIGNER. THE POTENTIAL USER AND/OR DESIGNER MUST MAKE FINAL ACCEPTANCE AND APPROVAL OF COMPONENTS AND SYSTEM AFTER TESTING PERFORMANCE ON WITHOUT WRITTEN PERMISSION FROM MICO. INC. AN ACTUAL APPLICATION FOR WHICH SYSTEM WAS DESIGNED.

THE MATERIAL DISCLOSED IN THIS DOCUMENT THIS DOCUMENT IS PROVIDED IN CONFIDENCE AND MAY NOT BE REPRODUCED OR DISCLOSED COPYRIGHT MICO, INC. ALL RIGHTS RESERVED. North Mankato, Minnesota U.S.A.

MULTIPLE DISC BRAKE 3C-141466-C24

9/24/98 GAA 10/08/03

CHECKED PART NUMBER REV 1: 2 LH 10/08/03 13-547-358 DRN G. J. APP FNO

G

PART NUMBER 13-547-358

Form No. 89-500-276 11-JUL-2002