



NOTES:

1. LINING REPAIR KIT P/N 12-501-004 2. BEARING REPAIR KIT P/N 12-501-006 3. O-RING REPAIR KIT P/N 12-501-002 4. SPRING REPAIR KIT P/N 12-501-008

SPECIFICATIONS:

WET MULTIPLE DISC BRAKE, SPRING APPLY, HYDRAULIC RELEASE
WET 3000 LBIN STATIC (BREAKAWAY) AT 0 PSI BACK PRESSURE
DRY 4500 LBIN DRY TORQUE FOR BRAKE RATING AND SPECIFICATIONS ONLY.
TORQUE RATING MAY VARY UP TO ±10% DUE TO MANUFACTURING TOLERANCES.
110 PSI INITIAL, 150 PSI FULL TYPE: TORQUE RATING:

RELEASE PRESSURE: MAXIMUM OPERATING PRESSURE: MAXIMUM SPEED: 3000 PSI 3900 RPM SINTERED BRONZE APPROXIMATE WEIGHT: 40 LBS

FOR USE WITH MINERAL BASE HYDRAULIC OIL ONLY

COOLING OIL RECOMMENDATIONS:

OIL TYPE: MINERAL BASE HYDRUALIC OIL SUCH AS MOBILE DTE 24. CITGO A/W 32 OR EQUVILENT FLOW THRU CAPACITY: 1.0 - 7.0 GPM MAXIMUM CASE PRESSURE: 15 PSI SUMP OIL VOLUME:

HORIZONTAL: 4 FL. OZ.

VERTICAL: CONTACT FACTORY

INCH [MILLIMETER]



COMPONENT AND SYSTEM RECOMMENDATIONS MADE BY MICO, MICO, INC CLAIMS PROPRIETARY RIGHTS TO INC ARE BASED ON INFORMATION SUPPLIED BY POTENTIAL USER AND/OR SYSTEM DESIGNER. THE POTENTIAL USER AND/OR DESIGNER MUST MAKE FINAL ACCEPTANCE AND APPROVAL OF AND MAY NOT BE REPRODUCED OR DISCLOSED COMPONENTS AND SYSTEM AFTER TESTING PERFORMANCE ON | WITHOUT WRITTEN PERMISSION FROM MICO, INC. AN ACTUAL APPLICATION FOR WHICH SYSTEM WAS DESIGNED. | COPYRIGHT MICO, INC. ALL RIGHTS RESERVED.

THE MATERIAL DISCLOSED IN THIS DOCUMENT. THIS DOCUMENT IS PROVIDED IN CONFIDENCE

0	SCALE 0.500	TITLE 3C-141445-CZ MULTIPLE DISC BRAKE			
E D	DWN MAP 2008-12-10	APVD PROD ENGRG PJS 2009-01-26	SIZE	DRAWING NUMBER	RE۱
	X NO	APVD ENGRG BLF 2008-12-11	В	13-547-362 CUSTOMER COPY	F 2 3