

NOTES:

USE MINERAL BASE HYDRAULIC DIL ONLY FOR BRAKE RELEASE
DIMENSIONS MAY VARY BETWEEN UNITS AND ARE FOR REFERENCE PURPOSES ONLY.
MILLIMETER VALUES MAY NOT BE AN EXACT CONVERSION OF INCH VALUES.

3. LINING REPAIR KIT P/N 12-501-286 4. BEARING REPAIR KIT P/N 12-501-006

5. O-RING REPAIR KIT P/N 12-501-002 6. SPRING REPAIR KIT P/N 12-501-008

SPECIFICATIONS:

DRY MULTIPLE DISC BRAKE. SPRING APPLY. HYDRAULIC RELEASE.

7.000 LBIN STATIC (BREAKAWAY) AT O PSI BACK PRESSURE TORQUE RATING:

160 PSI INITIAL, 210 PSI FULL RELEASE PRESSURE:

MAXIMUM OPERATING PRESSURE: 3.000 PSI MAXIMUM SPEED: 3.900 RPM SINTERED BRONZE LINING MATERIAL:

APPROXIMATE WEIGHT:

INCH [MILLIMETER]



COMPONENT AND SYSTEM RECOMMENDATIONS MADE BY MICO, MICO, INC CLAIMS PROPRIETARY RIGHTS TO INC ARE BASED ON INFORMATION SUPPLIED BY POTENTIAL THE MATERIAL DISCLOSED IN THIS DOCUMENT. USER AND/OR SYSTEM DESIGNER. THE POTENTIAL USER AND/OR THIS DOCUMENT IS PROVIDED IN CONFIDENCE DESIGNER MUST MAKE FINAL ACCEPTANCE AND APPROVAL OF AND MAY NOT BE REPRODUCED OR DISCLOSED COMPONENTS AND SYSTEM AFTER TESTING PERFORMANCE ON WITHOUT WRITTEN PERMISSION FROM MICO, INC. AN ACTUAL APPLICATION FOR WHICH SYSTEM WAS DESIGNED. | COPYRIGHT MICO, INC. ALL RIGHTS RESERVED.

)	SCALE 0.500				
· E			SIZE	DRAWING NUMBER	REV
)	2010-08-19 X N O	APVD ENGRG	R	13-547-392	_G
	X NO	RV 2010-08-23	U	CUSTOMER COPY	۰