

NOTES:

T. USE MINERAL BASE HYDRAULIC OIL ONLY FOR BRAKE RELEASE.

2. DIMENSIONS MAY VARY BETWEEN UNITS AND ARE FOR REFERENCE PURPOSES ONLY.

MILLIMETER VALUES MAY NOT BE AN EXACT CONVERSION OF INCH VALUES.

3. LINING REPAIR KIT P/N 12-501-004
4. BEARING REPAIR KIT P/N 12-501-006
5. O-RING REPAIR KIT P/N 12-501-002
6. SPRING REPAIR KIT P/N 12-501-008

SPECIFICATIONS:

DRY MULTIPLE DISC BRAKE, SPRING APPLY, HYDRAULIC RELEASE

TORQUE: 9-15 LBFT-

111

-7.125±.010 [180.98±.25]

2X 3.63 -[92.1]

2.254±.005 [57.25±.12] (TYP.)

4.508±.010 [114.50±.25] (TYP.)

TORQUE RATING: 4.500 LBIN STATIC (BREAKAWAY) AT 0 PSI BACK PRESSURE

RELEASE PRESSURE: 110 PSI INITIAL. 150 PSI FULL

MAXIMUM INPUT PRESSURE: 3.000 PSI MAXIMUM SPEED: 3,900 RPM SINTERED BRONZE LINING MATERIAL:

APPROXIMATE WEIGHT: 40 LB

INCH [MILLIMETER]

COMPONENT AND SYSTEM RECOMMENDATIONS MADE BY MICO, INC ARE BASED ON INFORMATION SUPPLIED BY POTENTIAL USER AND/OR SYSTEM DESIGNER. THE POTENTIAL USER AND/OR DESIGNER MUST MAKE FINAL ACCEPTANCE AND APPROVAL OF COMPONENTS AND SYSTEM AFTER TESTING PERFORMANCE ON AN ACTUAL APPLICATION FOR WHICH SYSTEM WAS DESIGNED.

MICO, INC CLAIMS PROPRIETARY RIGHTS TO THE MATERIAL DISCLOSED IN THIS DOCUMENT. THIS DOCUMENT IS PROVIDED IN CONFIDENCE AND MAY NOT BE REPRODUCED OR DISCLOSED WITHOUT WRITTEN PERMISSION FROM MICO, INC. COPYRIGHT MICO, INC. ALL RIGHTS RESERVED.



SCALE TITLE MULTIPLE DISC BRAKE 0.500 30 - 14 14 45 - 0 24 DRAWING NUMBER DWN SHYP APVD PROD ENGRG PJS 2014-12-30 13-547-424 APVD ENGR RV 10-27-2014 CUSTOMER COPY