



NOTES:

1. USE MINERAL BASE HYDRAULIC OIL ONLY FOR BRAKE RELEASE.
2. DIMENSIONS MAY VARY BETWEEN UNITS AND ARE FOR REFERENCE PURPOSES ONLY. MILLIMETER VALUES MAY NOT BE AN EXACT CONVERSION OF INCH VALUES.
3. REPAIR KIT P/N 12-501-429
4. O-RING REPAIR KIT P/N 12-501-523

SPECIFICATIONS:

TYPE:	DRY MULTIPLE DISC BRAKE, SPRING APPLY, HYDRAULIC RELEASE
TORQUE RATING:	8.000 LBIN STATIC (BREAKAWAY) AT 0 PSI BACK PRESSURE
RELEASE PRESSURE:	180 PSI INITIAL, 250 PSI FULL
MAXIMUM INPUT: OPERATING	3.000 PSI
MAXIMUM SPEED:	3.900 RPM
LINING MATERIAL:	SINTERED BRONZE
APPROXIMATE WEIGHT:	41 LB.

INCH
[MILLIMETER]

MICO [®] North Mankato, Minnesota USA				
SCALE 0.500	TITLE 3C-040080-R MULTIPLE DISC BRAKE	SIZE B	DRAWING NUMBER 13-547-498	REV C
DWNSHYPO 2015-04-07	APVD PROD ENGRG PJS 2015-04-07			
X NO	APVD ENGRG RV 2015-04-07		CUSTOMER COPY	3 5

COMPONENT AND SYSTEM RECOMMENDATIONS MADE BY MICO, INC ARE BASED ON INFORMATION SUPPLIED BY POTENTIAL USER AND/OR SYSTEM DESIGNER. THE POTENTIAL USER AND/OR DESIGNER MUST MAKE FINAL ACCEPTANCE AND APPROVAL OF COMPONENTS AND SYSTEM AFTER TESTING PERFORMANCE ON AN ACTUAL APPLICATION FOR WHICH SYSTEM WAS DESIGNED.

MICO, INC CLAIMS PROPRIETARY RIGHTS TO THE MATERIAL DISCLOSED IN THIS DOCUMENT. THIS DOCUMENT IS PROVIDED IN CONFIDENCE AND MAY NOT BE REPRODUCED OR DISCLOSED WITHOUT WRITTEN PERMISSION FROM MICO, INC. COPYRIGHT MICO, INC. ALL RIGHTS RESERVED.