



NOTES:

1. LINING REPAIR KIT P/N 12-501-004 2. BEARING REPAIR KIT P/N 12-501-006 3. O-RING REPAIR KIT P/N 12-501-002 4. SPRING REPAIR KIT P/N 12-501-008

SPECIFICATIONS:

WET MULTIPLE DISC BRAKE. SPRING APPLY. HYDRAULIC RELEASE WET 3000 LBIN STATIC (BREAKAWAY) AT 0 PSI BACK PRESSURE DRY 4500 LBIN DRY TORQUE FOR BRAKE RATING AND SPECIFICATIONS ONLY. 110 PSI INITIAL. 150 PSI FULL TORQUE RATING:

RELEASE PRESSURE: MAXIMUM OPERTATING

PRESSURF. 3000 PSI 3900 RPM SINTERED BRONZE LINING MATERIAL:

FOR USE WITH MINERAL BASE HYDRAULIC OIL ONLY

COOLING OIL RECOMMENDATIONS:

OIL TYPE: MINERAL BASE HYDRAULIC OIL SUCH AS MOBIL DTE 24. CITGO A/W 32 OR EQUIVALENT FLOW THRU CAPACITY: 1.0 - 7.0 GPM MAXIMUM CASE PRESSURE: 15 PSI

SUMP OIL VOLUME:

HORIZONTAL: 4 FL. OZ.

VERTICAL: CONTACT FACTORY

INCH [MILLIMETER]



COMPONENT AND SYSTEM RECOMMENDATIONS MADE BY MICO. MICO, INC CLAIMS PROPRIETARY RIGHTS TO INC ARE BASED ON INFORMATION SUPPLIED BY POTENTIAL USER AND/OR SYSTEM DESIGNER. THE POTENTIAL USER AND/OR DESIGNER MUST MAKE FINAL ACCEPTANCE AND APPROVAL OF AND MAY NOT BE REPRODUCED OR DISCLOSED COMPONENTS AND SYSTEM AFTER TESTING PERFORMANCE ON | WITHOUT WRITTEN PERMISSION FROM MICO, INC. AN ACTUAL APPLICATION FOR WHICH SYSTEM WAS DESIGNED. | COPYRIGHT MICO, INC. ALL RIGHTS RESERVED.

THE MATERIAL DISCLOSED IN THIS DOCUMENT. THIS DOCUMENT IS PROVIDED IN CONFIDENCE

3C - 212145-C Z SCALE MULTIPLE DISC BRAKE 0.500 APVD PROD ENGRG | SIZE | DRAWING NUMBER DWN MAP REV 2008-03-20 PJS 2009-04-20 13-547-526 X NO APVD ENGRG 08-2033 BLF 2008-11-07 CUSTOMER COPY