


NOTES:

- 1) FOR USE WITH MINERAL BASE HYDRAULIC OIL ONLY.
- 2) DIMENSIONS MAY VARY SLIGHTLY AND ARE FOR REFERENCES PURPOSE ONLY. MILLIMETER VALUES MAY NOT BE AN EXACT CONVERSION OF INCH VALUES
- 3) O-RING REPAIR KIT P/N 12-501-249
- 4) BEARING REPAIR KIT P/N 12-501-250
- 5) SPRING REPAIR KIT P/N 12-501-251
- 6) LINING REPAIR KIT P/N 12-501-306

SPECIFICATIONS:

TYPE:	DRY MULTIPLE DISC BRAKE, SPRING APPLY, HYDRAULIC RELEASE
RELEASE PRESSURE:	160 PSI INITIAL, 230 PSI FULL
TORQUE RATING:	12,000 LB-IN STATIC (BREAKAWAY) AT 0 PSI BACK PRESSURE
MAXIMUM OPERATING PRESSURE:	3,000 PSI
MAXIMUM SPEED:	3,900 RPM
LINING MATERIAL:	SINTERED BRONZE
APPROXIMATE WEIGHT:	52 LB

INCH
(MILLIMETER)



North Mankato, Minnesota USA

SCALE 0.500		TITLE MULTIPLE DISC BRAKE		
DWN RGS1 2008-10-30	APVD PROD ENGRG PJS 2009-02-10	SIZE B	DRAWING NUMBER 13-552-054	REV A
X NO X06-1154	APVD ENGRG BLF 2009-01-14	CUSTOMER COPY		

COMPONENT AND SYSTEM RECOMMENDATIONS MADE BY MICO, INC ARE BASED ON INFORMATION SUPPLIED BY POTENTIAL USER AND/OR SYSTEM DESIGNER. THE POTENTIAL USER AND/OR DESIGNER MUST MAKE FINAL ACCEPTANCE AND APPROVAL OF COMPONENTS AND SYSTEM AFTER TESTING PERFORMANCE ON AN ACTUAL APPLICATION FOR WHICH SYSTEM WAS DESIGNED.

MICO, INC CLAIMS PROPRIETARY RIGHTS TO THE MATERIAL DISCLOSED IN THIS DOCUMENT. THIS DOCUMENT IS PROVIDED IN CONFIDENCE AND MAY NOT BE REPRODUCED OR DISCLOSED WITHOUT WRITTEN PERMISSION FROM MICO, INC. COPYRIGHT MICO, INC. ALL RIGHTS RESERVED.