



**NOTES:**

- 1.) O-RING REPAIR KIT P/N 12-501-249
- 2.) BEARING REPAIR KIT P/N 12-501-333
- 3.) SPRING REPAIR KIT P/N 12-501-251
- 4.) LINING REPAIR KIT P/N 12-501-306

**SPECIFICATIONS:**

<b>TYPE:</b>	WET MULTIPLE DISC BRAKE, SPRING APPLY, HYDRAULIC RELEASE
<b>TORQUE RATING:</b>	WET 13,000 LB-IN STATIC (BREAKAWAY) AT 0 PSI BACK PRESSURE DRY 20,000 LB-IN DRY TORQUE FOR BRAKE RATING & SPECIFICATIONS ONLY
<b>RELEASE PRESSURE:</b>	270 PSI INITIAL, 380 PSI FULL
<b>MAXIMUM OPERATING PRESSURE:</b>	3,000 PSI
<b>MAXIMUM SPEED:</b>	3,900 RPM
<b>APPROXIMATE WEIGHT:</b>	52 LBS.
FOR USE WITH MINERAL BASE HYDRAULIC OIL ONLY.	

MICO, INC. CLAIMS PROPRIETARY RIGHTS TO THE MATERIAL DISCLOSED IN THIS DOCUMENT. THIS DOCUMENT IS PROVIDED IN CONFIDENCE AND MAY NOT BE REPRODUCED OR DISCLOSED WITHOUT WRITTEN PERMISSION FROM MICO, INC. COPYRIGHT MICO, INC. ALL RIGHTS RESERVED.

<b>mico</b> North Mankato, Minnesota U. S. A.		
SCALE 1:2	PART NUMBER 13-552-068	REV. B
X NO. X6433	CUSTOMER COPY	
DRAWN G. J.		
REVISED		
DATE 5/4/98	CHECKED	APPROVED ENG.