





## **NOTES**:

1. USE MINERAL BASE HYDRAULIC OIL ONLY FOR BRAKE RELEASE.
2. DIMENSIONS WITHOUT TOLERANCE MAY VARY BETWEEN UNITS AND ARE FOR REFERENCE PURPOSES ONLY.
MILLIMETER VALUES MAY NOT BE AN EXACT CONVERSION OF INCH VALUES.
3. LINING REPAIR KIT P/N 12-501-506
4. BEARING REPAIR KIT P/N 12-501-507

5. O-RING REPAIR KIT P/N 12-501-508 6. SPRING REPAIR KIT P/N 12-501-509

TO PREVENT BINDING, RUN THE BOLTS IN ALTERNATELY UNTIL SNUG.

TO PREVENT BINDING, RUN THE BOLTS IN ALTERNATELY UNTIL SNUG.

TORQUE 3/4" DIA. GRADE 8 BOLTS TO 285-315 LBFT. USE SUITABLE LOCTITE ON THE BOLT THREADS.

WHEN BRAKE IS MOUNTED TO A MOTOR, ALL AVAILABLE MOUNTING HOLES MUST BE USED.

## **SPECIFICATIONS:**

DRY MULTIPLE DISC BRAKE, SPRING APPLY, HYDRAULIC RELEASE

12,000 LBIN STATIC (BREAKAWAY) AT 0 PSI BACK PRESSURE ACTUAL TORQUE MAY VARY BY UP TO 10% DUE TO MANUFACTURING TOLERANCES. TORQUE RATING:

RELEASE PRESSURE: 160 PSI INITIAL, 230 PSI FULL

MAXIMUM OPERATING 3,000 PSI

PRESSURE:

MAXIMUM SPEED: 3.900 RPM LINING MATERIAL: SINTERED BRONZE

APPROXIMATE WEIGHT: 52 LB

INCH [MILLIMETER]

COMPONENT AND SYSTEM RECOMMENDATIONS MADE BY MICO,

INC. ARE BASED ON INFORMATION SUPPLIED BY POTENTIAL

USER AND/OR SYSTEM DESIGNER. THE POTENTIAL USER AND/OR

DESIGNER MUST MAKE FINAL ACCEPTANCE AND APPROVAL OF

COMPONENTS AND SYSTEM AFTER TESTING PERFORMANCE ON

AN ACTUAL APPLICATION FOR WHICH SYSTEM WAS DESIGNED.

THE MATERIAL DISCLOSED IN THIS DOCUMENT. DWN MG THIS DOCUMENT IS PROVIDED IN CONFIDENCE AND MAY NOT BE REPRODUCED OR DISCLOSED WITHOUT WRITTEN PERMISSION FROM MICO, INC.

COPYRIGHT MICO, INC. ALL RIGHTS RESERVED.

a WABCO company

MULTIPLE DISC BRAKE APVD PROD ENGRG DRAWING NUMBER MG 2017-07-24 13-552-116 APVD ENGR X09-3332 CL 2017-05-17 CUSTOMER COPY

01-MAR-2016