



- NOTES:**
- FOR USE WITH MINERAL BASE HYDRAULIC OIL ONLY.
  - SPRING REPAIR KIT P/N 12-501-461
  - LINING REPAIR KIT P/N 12-501-462
  - BEARING REPAIR KIT P/N 12-501-463
  - O-RING REPAIR KIT P/N 12-501-464
  - ADD 5.5 FL. OZ. MINERAL BASE HYDRAULIC OIL FOR SUMP COOLING.

**SPECIFICATIONS:**

TYPE:	WET MULTIPLE DISC BRAKE, SPRING APPLY, HYDRAULIC RELEASE
TORQUE RATING:	18,000 LBIN STATIC (BREAKAWAY) AT 0 PSI BACK PRESSURE
RELEASE PRESSURE:	330 PSI INITIAL, 450 PSI FULL
MAXIMUM OPERATING PRESSURE:	3,000 PSI
MAXIMUM SPEED:	3,900 RPM.
LINING MATERIAL:	SINTERED BRONZE
APPROXIMATE WEIGHT:	40 LB

**INCH**  
**(MILLIMETER)**

**MICO**  
North Mankato, Minnesota USA

SCALE 0.500	TITLE WHEEL MOUNT BRAKE	SIZE B	DRAWING NUMBER 13-587-102	REV B
DWN CL 2009-06-02	APVD PROD ENGRG PJS 2009-07-07	B	13-587-102	B
X NO 09-3003	APVD ENGRG RV 2009-06-16			

COMPONENT AND SYSTEM RECOMMENDATIONS MADE BY MICO, INC ARE BASED ON INFORMATION SUPPLIED BY POTENTIAL USER AND/OR SYSTEM DESIGNER. THE POTENTIAL USER AND/OR DESIGNER MUST MAKE FINAL ACCEPTANCE AND APPROVAL OF COMPONENTS AND SYSTEM AFTER TESTING PERFORMANCE ON AN ACTUAL APPLICATION FOR WHICH SYSTEM WAS DESIGNED.

MICO, INC CLAIMS PROPRIETARY RIGHTS TO THE MATERIAL DISCLOSED IN THIS DOCUMENT. THIS DOCUMENT IS PROVIDED IN CONFIDENCE AND MAY NOT BE REPRODUCED OR DISCLOSED WITHOUT WRITTEN PERMISSION FROM MICO, INC. COPYRIGHT MICO, INC. ALL RIGHTS RESERVED.