

NOTES:

1) LINING REPAIR KIT P/N 12-501-136

2) 0-RING REPAIR KIT P/N 12-501-134

3) SPRING REPAIR KIT P/N 12-501-138

4) LUBRICATE ALL STATORS AND THE PRIMARY WITH A RUST-PREVENTATIVE OIL BEFORE ASSEMBLING

SPECIFICATIONS:

TYPE: WET MULTIPLE DISC BRAKE, SPRING APPLY, HYDRAULIC RELEASE TORQUE RATING: 5,000 IN. LBS. STATIC (BREAKAWAY) AT 0 P.S. I. BACK PRESSURE

RELEASE PRESSURE: 140 P.S. I. INITIAL, 180 P.S. I. FULL

MAXIMUM OPERATING PRESSURE:

3,000 P.S.I. MAXIMUM SPEED: 3, 900 R. P. M.

LINING MATERIAL: SINTERED BRONZE

<u>APPROXIMATE WEIGHT:</u> 26 LBS.

FOR USE WITH MINERAL BASE HYDRAULIC OIL ONLY

COMPONENT AND SYSTEM RECOMMENDATIONS MADE BY MICO, MICO, INC CLAIMS PROPRIETARY RIGHTS TO INC ARE BASED ON INFORMATION SUPPLIED BY POTENTIAL THE MATERIAL DISCLOSED IN THIS DOCUMENT. USER AND/OR SYSTEM DESIGNER. THE POTENTIAL USER AND/OR DESIGNER MUST MAKE FINAL ACCEPTANCE AND APPROVAL OF AND MAY NOT BE REPRODUCED OR DISCLOSED COMPONENTS AND SYSTEM AFTER TESTING PERFORMANCE ON WITHOUT WRITTEN PERMISSION FROM MICO. INC.

THIS DOCUMENT IS PROVIDED IN CONFIDENCE AN ACTUAL APPLICATION FOR WHICH SYSTEM WAS DESIGNED. COPYRIGHT MICO, INC. ALL RIGHTS RESERVED.

,	SCALE FULL	TITLE MF-850-Z BRAKE MODULE				
		APVD PROD ENGRG	SIZE	DRAWING	NUMBER	REV
	1-29-90 X NO	APVD ENGRG	В	21-10	0-012	С
	/\ 1\ 0	74 TB ENGINO		CUSTOMER COPY		