



NOTES:

- 1) LINING REPAIR KIT P/N 12-501-267
- 2) O-RING REPAIR KIT P/N 12-501-268
- 3) SPRING REPAIR KIT P/N 12-501-269
- 4) LUBRICATE ALL STATORS AND THE PRIMARY WITH A RUST-PREVENTATIVE OIL BEFORE ASSEMBLING

SPECIFICATIONS:

TYPE: WET MULTIPLE DISC BRAKE, SPRING APPLY, HYDRAULIC RELEASE

TORQUE RATING: 5,000 IN. LBS. STATIC (BREAKAWAY) AT 0 P. S. I. BACK PRESSURE

RELEASE PRESSURE: 140 P. S. I. INITIAL, 180 P. S. I. FULL

MAXIMUM OPERATING PRESSURE: 3,000 P. S. I.

MAXIMUM SPEED: 3,900 R. P. M.

LINING MATERIAL: SINTERED BRONZE

APPROXIMATE WEIGHT: 26 LBS.

FOR USE WITH MINERAL BASE HYDRAULIC OIL ONLY



COMPONENT AND SYSTEM RECOMMENDATIONS MADE BY MICO, INC ARE BASED ON INFORMATION SUPPLIED BY POTENTIAL USER AND/OR SYSTEM DESIGNER. THE POTENTIAL USER AND/OR DESIGNER MUST MAKE FINAL ACCEPTANCE AND APPROVAL OF COMPONENTS AND SYSTEM AFTER TESTING PERFORMANCE ON AN ACTUAL APPLICATION FOR WHICH SYSTEM WAS DESIGNED.

MICO, INC CLAIMS PROPRIETARY RIGHTS TO THE MATERIAL DISCLOSED IN THIS DOCUMENT. THIS DOCUMENT IS PROVIDED IN CONFIDENCE AND MAY NOT BE REPRODUCED OR DISCLOSED WITHOUT WRITTEN PERMISSION FROM MICO, INC. COPYRIGHT MICO, INC. ALL RIGHTS RESERVED.

SCALE 1:1	TITLE CF-850-Z BRAKE MODULE	SIZE B	DRAWING NUMBER 21-100-026	REV C
DWN CEW 11-26-90	APVD PROD ENGRG	APVD ENGRG	CUSTOMER COPY	