

TITLEMULTIPLE DISC BRAKE MODULE PART NUMBER 21-100-108

> NPR OR ECO NO. DATE REV. ECO S-1324 03/17/99





## NOTES:

- 1) LINING REPAIR KIT P/N 20-060-103
- 2) 0-RING REPAIR KIT P/N 02-500-215
- 3) SPRING REPAIR KIT P/N 12-501-374

## **SPECIFICATIONS:**

WET MULTIPLE DISC BRAKE, SPRING APPLY, HYDRAULIC RELEASE

4,000 RPM SHAFT SPEED CAPABILITY SPECIFIED IS FOR BRAKE IN RELEASED CONDITION. ENERGY ABSORPTION DURING APPLY CYCLE MUST BE CAREFULLY EXAMINED MAXIMUM SPEED:

FOR EACH APPLICATION.

RELEASE PRESSURE: 105 PSI INITIAL, 120 PSI FULL, 3,000 PSI MAX.

1, 200 LB-IN STATIC (BREAKAWAY) TORQUE RATING:

VOLUME OF OIL REQUIRED TO RELEASE BRAKE: 0.5 IN.3 MIN., 0.9 IN.3 MAX.

APPROXIMATE WEIGHT: 19 LBS.

FOR USE WITH MINERAL BASE HYDRAULIC OIL ONLY.

## **CAUTION!**

IF HYDROSTATIC BENCH TESTING IS PERFORMED ON BRAKE ASSEMBLY, RELEASE PRESSURE SHOULD NOT EXCEED 400 P.S. I. UNLESS FOUR ADDITIONAL BOLTS (GRADE 5 OR BETTER) ARE USED FOR SUPPLEMENTAL ČLAMPING.

> MICO, INC. CLAIMS PROPRIETARY RIGHTS TO THE MATERIAL DISCLOSED IN THIS DOCUMENT. THIS DOCUMENT IS PROVIDED IN CONFIDENCE AND MAY NOT BE REPRODUCED OR DISCLOSED WITHOUT WRITTEN PERMISSION FROM MICO, INC. COPYRIGHT MICO, INC. ALL RIGHTS RESERVED.



SCALE 1: 2 PART NUMBER X NO. 21-100-108 DRAWN ETM D CUSTOMER COPY REVISED G.J. APPROVED ENG. DATE 03/17/99 CHECKED

Form No. 89-500-276 Rev. Initial