



NOTES:

- 1) FOR USE WITH MINERAL BASE HYDRAULIC OIL ONLY.
- 2) INSTALL THE CARTRIDGE AT THE INSTALLATION TORQUE SHOWN.
- 3) REPAIR KIT 06-400-223
- 4) EXTERNAL FILTRATION OF 10 MICRON OR BETTER IS REQUIRED.



COMPONENT AND SYSTEM RECOMMENDATIONS MADE BY MICO, INC ARE BASED ON INFORMATION SUPPLIED BY POTENTIAL USER AND/OR SYSTEM DESIGNER. THE POTENTIAL USER AND/OR DESIGNER MUST MAKE FINAL ACCEPTANCE AND APPROVAL OF COMPONENTS AND SYSTEM AFTER TESTING PERFORMANCE ON AN ACTUAL APPLICATION FOR WHICH SYSTEM WAS DESIGNED.

MICO, INC CLAIMS PROPRIETARY RIGHTS TO THE MATERIAL DISCLOSED IN THIS DOCUMENT. THIS DOCUMENT IS PROVIDED IN CONFIDENCE AND MAY NOT BE REPRODUCED OR DISCLOSED WITHOUT WRITTEN PERMISSION FROM MICO, INC. COPYRIGHT MICO, INC. ALL RIGHTS RESERVED.

SCALE	TITLE			
1.000	CARTRIDGE-INVERSE SHUTTLE			
DWN MAP	APVD PROD ENGRG	SIZE	DRAWING NUMBER	REV
2014-06-18	DPD 2014-10-23	B	26-465-002	D
X NO	APVD ENGRG		CUSTOMER COPY	2*
X5483-50	PWB 2014-10-22			