



NOTES:

1. FOR USE WITH MINERAL BASE HYDRAULIC OIL ONLY.
2. DIMENSIONS MAY VARY BETWEEN UNITS AND ARE FOR REFERENCE PURPOSES ONLY.
MILLIMETER VALUES MAY NOT BE AN EXACT CONVERSION OF INCH VALUES.
3. LINING REPAIR KIT P/N 12-501-004
4. BEARING REPAIR KIT P/N 12-501-006
5. O-RING REPAIR KIT P/N 12-501-002
6. SPRING REPAIR KIT P/N 12-501-008

SPECIFICATIONS:

DRY MULTIPLE DISC BRAKE. SPRING APPLY. HYDRAULIC RELEASE 9.800 LBIN STATIC (BREAKAWAY) AT 0 PSI BACK PRESSURE 180 PSI INITIAL. 290 PSI FULL

TYPE:
TORQUE RATING:
RELEASE PRESSURE:
MAXIMUM OPERATING
PRESSURE:
MAXIMUM SPEED:
LINING MATERIAL:
APPROXIMATE WEIGHT: 3000 PSI 3900 RPM'S SINTERED BRONZE 40 LBS <u>INCH</u> [MILLIMETER]



DRAWING NUMBER

COMPONENT AND SYSTEM RECOMMENDATIONS MADE BY MICO, MICO, INC CLAIMS PROPRIETARY RIGHTS TO INC ARE BASED ON INFORMATION SUPPLIED BY POTENTIAL THE MATERIAL DISCLOSED IN THIS DOCUMENT. USER AND/OR SYSTEM DESIGNER. THE POTENTIAL USER AND/OR DESIGNER MUST MAKE FINAL ACCEPTANCE AND APPROVAL OF AND MAY NOT BE REPRODUCED OR DISCLOSED COMPONENTS AND SYSTEM AFTER TESTING PERFORMANCE ON | WITHOUT WRITTEN PERMISSION FROM MICO, INC. AN ACTUAL APPLICATION FOR WHICH SYSTEM WAS DESIGNED. | COPYRIGHT MICO, INC. ALL RIGHTS RESERVED.

THIS DOCUMENT IS PROVIDED IN CONFIDENCE

	SCALE	TITLE			
•	0.500	MULTIPLE DISC BRAKE			
	DWN JRA	APVO PROD ENGRG PJS 2010-03-02	SIZE	DRAWING NUMBER	REV
١	2009-11-23 X NO	APVD FNGRG	B	13-547-280	В
	X08-2277-100			CUSTOMER COPY	2 1