



SECTION D-D
2 PLACES

INCH
[MILLIMETER]

- NOTES:**
- FOR USE WITH MINERAL BASE HYDRAULIC OIL ONLY. DIMENSIONS MAY VARY SLIGHTLY AND ARE FOR REFERENCES PURPOSE ONLY.
 - MILLIMETER VALUES MAY NOT BE AN EXACT CONVERSION OF INCH VALUES.
 - O-RING REPAIR KIT P/N 12-501-249
 - BEARING KIT P/N 12-501-250
 - SPRING REPAIR KIT P/N 12-501-251
 - LINING REPAIR KIT P/N 12-501-306

SPECIFICATIONS:

TYPE:	DRY MULTIPLE DISC BRAKE, SPRING APPLY, HYDRAULIC RELEASE
TORQUE RATING:	8,000 LBIN STATIC (BREAKAWAY) AT 0 PSI BACK PRESSURE
RELEASE PRESSURE:	100 PSI INITIAL, 170 PSI FULL
MAXIMUM OPERATING PRESSURE:	3,000 PSI
MAXIMUM SPEED:	3,900 RPM.
LINING MATERIAL:	SINTERED BRONZE
APPROXIMATE WEIGHT:	60 LB

FOR USE WITH MINERAL BASE HYDRAULIC OIL ONLY.



COMPONENT AND SYSTEM RECOMMENDATIONS MADE BY MICO, INC. ARE BASED ON INFORMATION SUPPLIED BY POTENTIAL USER AND/OR SYSTEM DESIGNER. THE POTENTIAL USER AND/OR DESIGNER MUST MAKE FINAL ACCEPTANCE AND APPROVAL OF COMPONENTS AND SYSTEM AFTER TESTING PERFORMANCE ON AN ACTUAL APPLICATION FOR WHICH SYSTEM WAS DESIGNED.	MICO, INC. CLAIMS PROPRIETARY RIGHTS TO THE MATERIAL DISCLOSED IN THIS DOCUMENT. THIS DOCUMENT IS PROVIDED IN CONFIDENCE AND MAY NOT BE REPRODUCED OR DISCLOSED WITHOUT WRITTEN PERMISSION FROM MICO, INC. COPYRIGHT MICO, INC., ALL RIGHTS RESERVED.	SCALE 0.500	TITLE 3D-131580-E MULTIPLE DISC BRAKE	REV A
DWN RGS1 2009-02-02	APVD ENGRG RV 2009-02-03	SIZE D	DRAWING NUMBER 13-552-100	CUSTOMER COPY